

STANLEY UNDERWATER GRINDER



PRODUCT DESCRIPTION	GR29
TYPE	Underwater Grinder
PRODUCT DESCRIPTION	
<ul style="list-style-type: none"> - The Stanley GR29 Grinder is used for top, face and side grinding using 9 inch (228.6 mm) diameter wheels. Wire brushes can be used and depressed-center wheels with an optional adapter. - Can be used for grinding and cleaning with either cup or standard grinding wheels, wire or nylon brushes. - The integral Stanley HYREVZ™ gear motor is manufactured to exacting standards to deliver maximum efficiency. - The plastisol covering the handle transmits very little heat. The plastisol gives more comfortable grip to the tool. - There are two positions available for the assist handle to be conveniently placed by the operator. Either position is at most comfortable handling position from the valve handle. - The wheel guard is adjustable. By loosening the clamp screw the guard may be rotated to any convenient position. 	

FEATURES
<ul style="list-style-type: none"> - 4-10 gpm (15-38 lpm) operating range - 2700 rpm @ 10 gpm (38 lpm) - Adjustable wheel guard - Integral HYREVZ™ gear-type motor - Assist handle



SPECIFICATIONS		
ITEM	U.S.A	METRIC
Capacity	9 in. wheel on 5/8 in. -11 Arbor	
RPM	2700 @ 10 gpm	2700 @ 38 lpm
Weight (with guard)	14 lb	6.4 kg
Length	11 in	28 cm
Width (with guard)	12 in	30.5 cm
Pressure	1000-2500psi	70-176 bar
Flow Range	4-10 gpm	15-38 lpm
Optimum Flow	10 gpm	38 lpm
Porting	-8 SAE O-ring	
Hose whips	No	
Motor	Stanley HYREVZ™ Gear	